



- **Handles pallets the hard way**
- **Quiet operation**
- **Low profile - 12" elevation optional**
- **Available with zero pressure accumulation feature**

STANDARD SPECIFICATIONS

Frame - 9" x 7 gauge powder painted formed steel channel frames. Sections are bolted together with splice plates and floor supports.

Chain - (2) 60F single pitch conveyor chains, straight side bar, on 36" centers.

Chain Guide - UHMW

Floor Supports - 24" to top of chain. One support supplied at each end of conveyor and at each bed joint.

Motor - 1 HP 230/460-3-60 TE motor, C-Face. Motor and speed reducer are located underneath conveyor frame.

Speed Reducer - Heavy duty worm gear for C-Faced mounted motor.

Sprockets - Hardened sprockets with 1¹⁵/₁₆" diameter CRS drive shaft.

Bearings - Sealed, pre-lubricated with cast iron housing.

Speed - 30 FPM constant speed.

Capacity - 10,000 lbs. maximum distributed live load at 30 FPM. Maximum motor size 3 HP.

OPTIONAL EQUIPMENT

Elevation - 12" minimum (with adjustment to 13") to top of chain, made available by modification. Contact factory.

Motors - Single phase, energy efficient.

Chain Centers - Other chain centers and multiple chains available, 18" minimum chain centers. Contact factory.

Speeds - For speeds greater than 30 FPM, contact factory.

Electrical Controls - Magnetic starters and push button stations; manual motor starters with overload protection, others.

MODEL "DC"



Overall Length	Frame Width	20"	26"	32"	38"	44"	50"
	Chain Center	18"	24"	30"	36"	42"	48"
10'	Weights (in lbs.)	540	585	630	678	723	768
15'		726	790	855	918	983	1048
20'		911	995	1080	1158	1243	1328
25'		1096	1200	1305	1398	1503	1608
30'		1281	1405	1530	1638	1763	1888
35'		1466	1610	1755	1878	2023	2168
40'		1651	1815	1980	2118	2283	2446
45'		1836	2020	2205	2358	2543	2728
50'		2021	2225	2430	2598	2803	3008
55'		2206	2430	2655	2838	3063	3288
65'		2576	2840	3105	3318	3583	3848
75'		2946	3250	3555	3798	4103	4408
85'		3316	3660	4005	4248	4623	4968
95'		3686	4070	4455	4698	5143	5528
105'		4056	4480	4905	5148	5663	6088

Load Capacity Chart

HP	30 FPM WITH 2 STRANDS	
	TOTAL LIVE LOAD (lbs.)	
	Up to 50'	Up to 100'
1	4,000	3,000
2	6,500	6,000
3	10,000	9,500

